



Technical data for StandardLine (electrodes)

A higher humidification performance is possible by connecting units together.

Type	SLE02	SLE05	SLE10	SLE15	SLE20	SLE30	SLE45	SLE65	
Steam output [kg/h]	1.9 - 2.1	4.4 - 4.8	4.8 - 5.2	9.5 - 10.4	14.3 - 15.6	19.0 - 20.7	28.5 - 31.2	42.7 - 46.8	62.0 - 67.5
Electrical connection	220-240V / 1 / N / 50-60 Hz		380-415V / 3 / 50-60Hz ⁽¹⁾						
Electrical power [kW]	1.4 - 1.6	3.3 - 3.6	3.6 - 3.9	7.1 - 7.8	10.7 - 11.7	14.3 - 15.5	21.4 - 23.4	32.0 - 35.1	46.3 - 50.6
Rated current [A]	6.5	15.0	5.4	10.8	16.3	21.7	32.5	48.8	70.4
Fuse [A] ⁽²⁾	1 x 10	1 x 16	3 x 10	3 x 16	3 x 20	3 x 35	3 x 40	3 x 63	3 x 80
Number of cylinders	1								
Control	StandardLine								
Control voltage [V]	220 - 240 separate (internal control voltage optionally at extra charge)								
Steam hose connection [mm]	1 x 25				1 x 40		2 x 40		
Condensate hose connection [mm]	1 x 9	1 x 12				2 x 12			
Weight (empty) [kg]	9	12		20		39	41		
Weight (operating) [kg]	12	17		34		75	77		
Dimensions WxHxD [mm] ⁽³⁾	350 x 375 x 245	350 x 535 x 245		425 x 695 x 320		590 x 790 x 415			
Water supply	Tap water of different qualities 1 to 10 bar (100 x 10 ³ to 1000 x 10 ³ Pa), for 3/4" external thread								
Waste water connection	Connecting piece Ø 1 1/4"								

Subject to technical changes.

- ⁽¹⁾ Other voltages upon request.
⁽²⁾ 1.1-fold the power consumption after full blowdown.
 Pay attention to the automatic triggering of the circuit breakers.
 If required, select the next highest circuit breaker level.
⁽³⁾ Outer width and depth dimensions. Height including drain connection.



HygroMATIK[®]
 member of CAREL group 

HygroMatik GmbH
 Lise-Meitner-Str. 3
 24558 Henstedt-Ulzburg
 Germany
 T +49 4193 895-0
 F +49 4193 895-33
 hy@hygromatik.de
 www.hygromatik.com