

## Technical Data HeaterSlim

Type	HS06		HS10	
Steam output [kg/h]	6.6		10.0	
Electrical connection	220-240V / 1Ph / N / 50-60Hz	380-415V / 3Ph / N / 50-60Hz	220-240V / 1Ph / N / 50-60Hz	380-415V / 3Ph / N / 50-60Hz
Rated power [kW]	5.0		7.5	
Rated current [A]	21.7	10.9	32.6	10.9
Fuse [A]	1 x 25	2 x 16	1 x 35	3 x 16
Number of steam cylinder	1			
Steam hose connection [mm]	1 x 40			
Empty weight [kg]	13.5		13.7	
Max. filling capacity [l]	3.0		3.0	
Operating weight [kg]	18.0		18.0	
Dimensions WxHxD [mm] (1)	580 x 370 x 170			
Water connection	Fully demineralised water / cleaned condensate / partially softened water / tap water of varying qualities, 1 -10 bar, for 3/4" external thread			
Drain water connection	Connection Ø 1 1/4"			

**We reserve the right to make technical changes.**

(1) Outer dimensions of width and depth.  
Height incl. drain connection.

## Our service for you

- HygroMatik distributors in more than 45 countries worldwide
- Technical hotline +49 4193 859 - 293 or [hotline@hygromatik.com](mailto:hotline@hygromatik.com)
- Manuals, planning tools and workshop offers are available online at [www.hygromatik.com](http://www.hygromatik.com)



**HygroMATIK** ® SPA  
member of CAREL group 

HygroMatik GmbH  
Lise-Meitner-Str. 3  
24558 Henstedt-Ulzburg  
Germany

T +49 4193 895-0  
F +49 4193 895-33  
[hy@hygromatik.de](mailto:hy@hygromatik.de)  
[www.hygromatik.com](http://www.hygromatik.com)